


**NEW
PRODUCT
RANGE FOR 2010**


VELUX®

World leading skylights and roof windows


Product information and price list April 2010



**STREAMLINED
EXTERIOR**



**ALL NEW AND
IMPROVED SKYLIGHTS**




**WHITE
INTERIOR
FINISH**



**INTELLIGENT
CONTROL**



**IMPROVED PERFORMANCE
MORE LIGHT - LESS HEAT**



**SOLAR
POWERED
BLINDS**

**NO PRICE
INCREASES**

Throughout the construction industry, VELUX is a by-word for quality, a reputation that has been painstakingly built up for more than 25 years in Australia and for over 65 years around the world.

Perfectly designed to withstand the world's harshest climatic conditions, all VELUX products are of the highest quality and will perform superbly for a lifetime of faultless service.

Take a look through this guide and judge for yourself. For range, quality, value, guarantees, delivery and service – VELUX is a world leader.

Guaranteed to last...

✓ **10 Year Warranty** on all skylights and roof windows.

✓ **3 Year Warranty** on accessories, including electric controls.

VELUX skylights and roof windows are included in the National Energy Rating programme (AccuRate) as well as State run programmes such as Basix & FirstRate.

Tested and approved to Australian Standards

When installing VELUX skylights 3m or higher above floor level, 2004 High Performance glazing must be used to comply with Australian Standard AS 1288 (i.e. sloped overhead glazing must be laminated glass).

Surpasses Australian tests for skylights

AS4285 SKYLIGHTS



Cyclonic & Non-Cyclonic

AS1288 OVERHEAD GLAZING



Laminated inner pane†

AS3959 BUSHFIRE



Attack Level 40†

Window Energy Rating Scheme (WERS)

(MAXIMUM 5 ON WERS SUMMER RATING)



Building Code compliance

All VELUX skylights/roof windows (except sun tunnels) are deemed non-combustible and thereby comply with BCA Fire Separation requirements (i.e. suitable for use within 900mm from allotment boundary/separation wall)*.

* CSIRO assessment report available on request. VELUX recommends consultation with relevant authority before work commences.

† 2004 glazing variant



Manual Skylights Page 5

NEW



Electric Skylights Page 5

NEW




Fixed Skylights Page 7

NEW



VELUX new generation skylights Letting more light in without the heat




Roof Windows Page 9



Centre-Pivot or dual action

Sun Tunnels Page 11



Rigid or flexible versions

Flat Roof Skylights Page 13

NEW




Domestic or commercial

Controlling daylight and fresh air



NEW IMPROVED MODEL






VELUX VS Manually operated top-hung skylights

Provides the comfort and energy savings of free daylight and natural ventilation.

- New white painted interior wood frame and sash, with outer aluminium cappings.
- Operated by base handle, for within reach situations, or by rod for out-of-reach use (to 285cm above head height).
- Flyscreen fitted as standard.
- Choice of 8 sizes.
- New streamlined exterior – smooth low profile sits lower in the roof, does not obstruct the roofline.
- High performance or Comfort double glazing on most sizes.
- Maximum 5 stars on WERS Summer rating.
- Complete with flashings for corrugated iron or tile roofs.
- Improved U-value (2.5 W/m²K S06 size complete skylight).[†]
- Improved Solar Heat Gain co-efficient (0.21 for S06 size, complete skylight).[†]

Control options

- Window handle for operating within-reach skylights. 
- Telescopic rod control for out-of-reach situations. (145cm in length, extendable up to 285cm.) 
- Short control rod. 60cm long. 

Blind options – All tailor-made to fit each size of skylight

NEW VS Solar Powered Blockout – includes hand-held remote (wall-mounted keypad from June/July 2010).

VS Electric Venetian – requires KLR 100 remote control and KLC 500 multi controller


• All blinds are available in white. • Now even easier to fit using VELUX *Pick&Click!*™ System.

*For roofs below 15° pitch, skylights need to be raised to 15° and custom flashed. VELUX can assist with technical advice and drawings on this type of installation.

†U-value and SHGC data based on AFRC simulations for 2004 glazing.

SIZES AND PRICES – PAGE 14

NEW IMPROVED MODEL



VELUX VSE Electronically operated top-hung skylights

The ultimate skylight that provides abundant daylight and controllable ventilation.

- New white painted interior wood frame and sash, with outer aluminium cappings.
- Complete with pre-installed electric motor, new control system and rain sensor.
- Simple to install – 2 metre lead (supplied) plugs straight into power point.
- New streamlined exterior – smooth low profile sits lower in the roof, does not obstruct the roofline.
- Choice of 8 sizes.
- High performance double glazing as standard.
- Flyscreen fitted as standard.
- Maximum 5 stars on WERS Summer rating.
- Complete with flashings for corrugated iron or tile roofs.
- Improved U-value (2.5 W/m²K S06 size complete skylight).[†]
- Improved Solar Heat Gain co-efficient (0.21 for S06 size, complete skylight).[†]

NEW wireless control system

- Self programming radio frequency remote with advanced control options for both skylights and blind operation.
- Externally mounted rain sensor automatically closes the skylight once rain is detected.



VSE Electric Blockout – uses VSE remote control

VSE Electric Venetian – uses VSE remote control




Outstanding daylight provision

where extra ventilation is not required



NEW IMPROVED MODEL



VELUX FS

Fixed skylights

Cost effective for creating light-filled rooms where adequate ventilation already exists. Energy efficient glazing and the use of blinds ensures heat transference is minimised.

- New white painted interior wood frame and sash, with outer protective aluminium cappings.
- Flashings for corrugated iron or tile roofs.
- High performance or Comfort double glazing on most sizes.
- New streamlined exterior – smooth low profile sits lower in the roof, does not obstruct the roofline.
- Maximum 5 stars on WERS Summer rating.
- Available in 8 sizes.
- Improved U-value, (2.6 W/m²K S06 size complete skylight).[†]
- Improved Solar Heat Gain co-efficient (0.24 for S06 size, complete skylight).[†]

Blind options –

All tailor-made to fit each size of skylight

NEW FS Manual Blockout – requires rod control for out-of-reach

FS Manual Venetian – requires rod control for out-of-reach

NEW FS Solar Powered Blockout – includes hand-held remote (wall-mounted keypad from June/July 2010).

FS Electric Venetian – requires KLR 100 remote control and KLC 500 multi controller

- All blinds are available in white.
- Now even easier to fit using VELUX *Pick&Click!*™ System.

*For roofs below 15° pitch, skylights need to be raised to 15° and custom flashed. VELUX can assist with technical advice and drawings.


[†]U-value and SHGC data based on AFRC simulations for 2004 glazing.

SIZES AND PRICES – PAGE 14

NEW IMPROVED LOW-E³ COATING

Glazing Options

High performance double glazing (2004)




Benefits:

- Radiant heat block 80%
- UV rays block 99%
- Noise reduction factor 32 decibels
- WERS rating 5 stars
- Double layer of Low-E³ coating.
- 10 year warranty on insulated glass seal.

AS1288

2004 glass must be used for skylights installed 3m or more above floor level.

Comfort double glazing (2005)



Benefits:

- Radiant heat block 80%
- UV rays block 95%
- Noise reduction factor 29 decibels
- WERS rating 5 stars
- Double layer of Low-E³ coating.
- 10 year warranty on insulated glass seal.

GGL/GHL window pane tint (i.e. colouration) is slightly different to skylight window pane tint.



Transform wasted attic space into fantastic loft living



VELUX GGL Centre-Pivot roof window

Beautifully engineered for a lifetime of use, the GGL is ideal for in-reach attic situations where furniture can be positioned beneath the window.

- A short pull on the top control bar allows filtered background ventilation even while the window remains shut.
- A second pull on the control bar allows the window to rotate for maximum ventilation – and up to 180° for cleaning the outer pane from inside the room.
- Quality lacquered pine sash and frame.
- Complete with outer aluminium cappings and flashings for corrugated iron or tile roofs.
- Available in 4 sizes.
- High performance double glazing as standard.
- Insect screen available as optional extra.



VELUX GHL Dual action roof window

Developed for use in attics with shallower pitched roofs to maximise roof top views.

- For within-reach situations.
- Opens in two ways: the bottom handle allows for top-hung opening; while a short pull on the top control bar operates the filtered vent flap for background ventilation even while the window is shut. A longer pull allows the sash to rotate 180° for ease of cleaning the outer pane from inside the room.
- Quality lacquered pine sash and frame.
- Complete with outer aluminium cappings and flashings for corrugated iron or tile roofs.
- Available in 4 sizes.
- High performance double glazing as standard.
- Insect screen available as optional extra.

NEW

Blind options – All tailor-made to fit each size of roof window

GGL Manual Blockout

GGL Manual Venetian

GHL Manual Blockout

GHL Manual Venetian

• All blinds only available in white • Now even easier to fit using VELUX **Pick&Click!**™ System.

VELUX GDL CABRIO™ Balcony roof window

When closed it looks just like an ordinary skylight – but within seconds it opens up to a fantastic roof top balcony.

Bottom section moves forward and locks upright with integral banister railings to form a sturdy balcony surround.

*For roofs below 15° pitch, skylights need to be raised to 15° and custom flashed. VELUX can assist with technical advice and drawings.



SIZES AND PRICES – PAGE 15




VELUX Blinds – effective light control

VELUX has a choice of blinds that provide different levels of light control. Tailor-made to fit perfectly to each size of skylight or roof window, they are easy to install and are supplied with aluminium side channels that allow the blind to be positioned at any point down the window.

10

Blockout blinds



Provide complete blockout from light. Manual, electric or Solar powered versions available.

- Blind can be stopped at any position on the window.
- Reduce light by approx 100%.
- Available in white only.

Venetian blinds



Control the amount and direction of light. Manual or electric versions available.

- Aluminium slats, white on inner and outer surfaces.
- Reduce light by up to 85%.

Pick&Click!™



The new innovative VELUX **Pick&Click!**™ system makes installing our blinds a snap!

Blind options

	Manual Blockout	Manual Venetian	Solar Blockout	Electric Blockout	Electric Venetian
FS	✓ [^]	✓ [^]	✓ [*]		✓ [°]
VS			✓ [*]		✓ [°]
VSE				✓ [†]	✓ [†]
GGL	✓	✓			
GHL	✓	✓			

NB: New VELUX blinds and flashings do not fit VELUX skylights manufactured prior to March 2010 and must be ordered accordingly.

[^] Manual blinds for Fixed Skylights need rod control for out-of-reach situations (ZXT 200).

^{*} Solar powered blinds include hand-held remote (wall-mounted keypad supplied from June/July 2010).

[†] Uses VSE remote control (see page 5).

[°] Needs KLR 100 and KLC 500 control.

Blinds are not available for FCM flat roof skylights.

BLINDS PRICES – PAGE 15



15°-60°
INSTALLATION PITCH*

VELUX Sun Tunnels

Bringing natural light into places you never thought possible!


VELUX Sun Tunnels are like no others on the market, because they use a toughened glass, fixed skylight within the roof structure.

The outer frame has the appearance of a traditional skylight and sits flush with the roof for harmonious effect.

By using glass not plastic, the outer pane will not discolour with age and so affect the quality of light.

VELUX Sun Tunnels are ideal for dim or dark places such as corridors, stairwells and toilets.

11



BATHROOMS, EN-SUITES CORRIDORS AND STAIRWELLS DAYLIGHT WHERE YOU WANT

AFTER

BEFORE

Packages come complete with:


- Choice of highly reflective flexible or rigid tunnel (350mm diameter, lengths vary – see price list on page 15).
- 4mm toughened glass.
- Dual-layered ceiling diffuser – spreads light over an area of up to 9m².
- White ceiling ring.
- Outer aluminium & PVC cappings and integral flashings for tiled roofs.
- Straight forward to install.
- 7 year warranty.

*Sun Tunnels are not suitable for roof pitches below 15°.

Versatile daylighting for flat roofs



NEW IMPROVED MODEL



VELUX FCM Flat roof, glazed skylight


The brilliantly simple FCM flat roof skylight incorporates the VELUX High performance glazing unit and an all metal, insulated exterior frame.

The new smoother exterior gives not only a lower profile on the roof, but also provides a "cool" daylighting solution by effectively blocking heat build up and UV rays.

Huge benefits at a fraction of the price you would expect.

- Unlike acrylic or polycarbonate – glass will not fade or discolour over time.
- VELUX High performance glazing blocks 80% of radiant heat and gives 99% protection from UV rays.

- Maintenance free anodized heavy-gauge aluminium frame withstands the extremes of the Australian climate.
- Maximum 5 stars on WERS Summer rating.
- Available in 7 sizes.
- Versatile positioning: most sizes can be used in portrait, landscape or even "diamond shape" orientation.
- High performance double glazing as standard.
- Improved U-value, (2.8 W/m²K 4646 size, complete skylight).†
- Improved Solar Heat Gain co-efficient (0.26 for 4646 size, complete skylight).‡
- Requires custom-made flashing (not supplied). VELUX can assist with Technical advice and drawings for this type of flashing.
- 10 year warranty.



Inner glass dimension, wxh mm	▶ 572 x 572	572 x 877	572 x 1181	572 x 1792	775 x 775	775 x 1181	1181 x 1181
Overall throat dimension for custom-made flashing, wxh mm	▶ 665 x 665	665 x 970	665 x 1275	665 x 1885	870 x 870	870 x 1275	1275 x 1275
Throat width must not exceed 35mm							
Size code	▶ FCM 2222	FCM 2234	FCM 2246	FCM 2270^	FCM 3030	FCM 3046	FCM 4646

^FCM 2270 not recommended for "landscape" orientation.
 *VELUX recommends FCM installed at a minimum pitch of 2° to prevent condensation build-up and to allow water run-off.
 †U-value and SHGC data based on NFRC simulations for 2004 glazing.

Openable Skylights

Page 5

Overall frame dimension w x h mm	550 x 700	550 x 980	550 x 1400	780 x 980	780 x 1180	780 x 1400	1140 x 700	1140 x 1180
New size code	C01	C04	C08	M04	M06	M08	S01	S06
(Old code)	(101)	(104)	(108)	(304)	(306)	(308)	(601)	(606)

NEW

Manual Skylights

VS 2005 Comfort double glazing (RRP) \$	826	835	945	960	-	1,160	-	-
VS 2004 High performance double glazing (RRP) \$	871	888	1,002	1,030	1,120	1,210	1,098	1,364

Package includes: Flashing for single skylight in corrugated iron or tile roof, insect screen and operating hook.
 NB: Operating Rod (ZCT 300) for out-of-reach operation and handle (ZZZ 201 for within-reach operation in place of hook) to be purchased separately.
 For roofs below 15° pitch, skylights need to be raised to 15° and custom flashed. VELUX can assist with technical advice and drawings on this type of installation.

Page 5

NEW

Electric Skylights

New size code	C01	C04	C08	M04	M06	M08	S01	S06
(Old code)	(101)	(104)	(108)	(304)	(306)	(308)	(601)	(606)

VSE 2004 High performance glazing (RRP) \$	1,910	1,934	2,045	2,072	2,161	2,249	2,157	2,400
--	-------	-------	-------	-------	-------	-------	-------	-------

Package includes: Flashing for single skylight in corrugated iron or tile roof, insect screen, pre installed electric motor, remote control and rain sensor. No additional electrical control system required when adding blinds. For roofs below 15° pitch, skylights need to be raised to 15° and custom flashed. VELUX can assist with technical advice and drawings on this type of installation.

Page 10

NEW

Blinds (For VS and VSE)

New size code	C01	C04	C08	M04	M06	M08	S01	S06
(Old code)	(101)	(104)	(108)	(304)	(306)	(308)	(601)	(606)

DSH Solar Blockout, Electric**, White (VS only) (RRP) \$	479	479	-	489	489	489	499	499
PMH Electric Venetian*, White (VSE & VS) (RRP) \$	482	496	511	501	518	533	511	547
DMH Electric Blockout, White (VSE only) (RRP) \$	494	512	-	513	523	544	522	560

*Additional electrical control system (KLC 500) and remote control (KLR 100) required for blinds on VS skylight.
 **Remote control supplied (wall-mounted keypad supplied from June/July 2010).

NB: New VELUX blinds and flashings do not fit previous VELUX skylights †

Fixed Skylights

Page 7

Overall frame dimension w x h mm	550 x 700	550 x 980	550 x 1400	780 x 980	780 x 1180	780 x 1400	1140 x 700	1140 x 1180
New size code	C01	C04	C08	M04	M06	M08	S01	S06
(Old code)	(101)	(104)	(108)	(304)	(306)	(308)	(601)	(606)

NEW

Fixed Skylights

FS 2005 Comfort double glazing (RRP) \$	397	489	606	574	-	690	-	-
FS 2004 High performance double glazing (RRP) \$	491	559	710	680	762	846	759	892

Package includes: Flashing for single skylight in corrugated iron or tile roof.
 For roofs below 15° pitch, skylights need to be raised to 15° and custom flashed. VELUX can assist with technical advice and drawings on this type of installation.

Page 10

NEW

Blinds (For FS)

New size code	C01	C04	C08	M04	M06	M08	S01	S06
(Old code)	(101)	(104)	(108)	(304)	(306)	(308)	(601)	(606)

PAD Manual Venetian**, White only (RRP) \$	165	180	200	190	210	225	200	240
DKD Manual Blockout**, White only (RRP) \$	175	190	210	200	220	235	210	250
PMD Electric Venetian*, White only (RRP) \$	468	480	510	500	516	531	513	552
DSD Solar Blockout, Electric***, White only (RRP) \$	479	479	-	489	489	489	499	499

*Additional electrical control system (KLC 500) and remote control (KLR 100) required.
 Requires ZXT 200 control rod for out of reach situations (at additional cost). * Remote control supplied (wall-mounted keypad supplied from June/July 2010).

Page 9

CABRIO™ Balcony Windows – for full product details and prices contact VELUX Customer Services

Prices include flashing for single skylight into tile or metal roof. Contact VELUX Customer Services for details and prices of combi flashings for coupled skylights.
 Price list effective April 2010. All prices are supply only and include GST. Prices subject to change without notice. All prices quoted are Recommended Retail Prices (RRP) only.

Delivery time (in working days)*	NSW 1-2	VIC 1-2	SA 3	ACT 1-2	QLD 2-5	NT 3-7	TAS 3-5	WA 1-2†
----------------------------------	---------	---------	------	---------	---------	--------	---------	---------

*Metropolitan areas only. Subject to order being processed before 12 EST noon. †Subject to availability at Perth warehouse.

‡New VELUX blinds and flashings do not fit VELUX skylights manufactured prior to March 2010 and must be ordered accordingly.

Openable Roof Windows

Page 9

Overall frame dimension w x h mm	550 x 780	550 x 980	780 x 980	780 x 1180	780 x 1400
Size code	C02	C04	M04	M06	M08

Manual Roof Windows

GGL Centre pivot, High performance double glazing (RRP) \$	690	730	845	-	1,020
GHL Dual action, High performance double glazing (RRP) \$	-	NEW 810	919	1,009	NEW 1,130

Package includes: Flashing for single window in corrugated iron or tile roof. Please enquire for details and prices of combi flashing (for coupled roof windows).
 For out-of-reach situations requiring manual operation, order ZCT 200 rod control (at additional cost).

ZIL Insect Screens (For GGL and GHL) (RRP) \$	239	239	294	294	294
---	-----	-----	-----	-----	-----

ZIL Insect Screen is fitted to plaster reveal. Suitable for within-reach applications only.

Page 10

Blinds (For GGL and GHL)

Size code	C02	C04	M04	M06	M08
-----------	------------	------------	------------	------------	------------

DKL Manual Blockout Blinds, White only (RRP) \$	176	189	195	208	228
PAL Manual Venetian Blinds, White only (RRP) \$	187	200	206	223	239


Page 5

Electric and Rod Controls

NEW ZZZ 201 Handle (white) to operate openable skylight within reach (see picture on page 5) (RRP) \$	36
ZOZ 032 Short rod control (60 cm) to operate within reach, manual openable skylight (RRP) \$	43
NEW ZXT 200 Rod control to operate manual fixed skylight blinds. 100cm in length – extendable up to 180cm (RRP) \$	50
ZCT 300 Rod control to operate manual openable skylight. 145cm in length – extendable up to 285cm (RRP) \$	58
NEW KLC 500 Multi controller to operate electric Blockout or electric Venetian blinds on a manual or fixed skylight. Operates up to 5 blinds. Must be used with KLR 100 remote control (RRP) \$	395
NEW KLR 100 Remote control, used with KLC 500 electric multi controller (RRP) \$	170

Page 11

Sun Tunnels



TWF 014 Sun Tunnel with flexible shaft – 2200mm long, 350mm diameter (RRP) \$	330
TWR 014 Sun Tunnel with rigid shaft – 1950mm long, 350mm diameter (RRP) \$	549
ZTR 014 Rigid extension – 1240mm (RRP) \$	220

Packages complete with integral flashing for tiled or corrugated iron roofs, tunnel, ceiling diffuser and ceiling ring (white). Sun Tunnels must be pitched at a minimum of 15°.

Page 12

NEW

Flat Roof Skylights

Inner glass dimension. w x h mm	572 x 572	572 x 877	572 x 1181	572 x 1792	775 x 775	775 x 1181	1181 x 1181
Overall throat dimension for custom-made flashing. w x h mm	665 x 665	665 x 970	665 x 1275	665 x 1885	870 x 870	870 x 1275	1275 x 1275
Throat width must not exceed 35mm							

Size code	FCM 2222	FCM 2234	FCM 2246	FCM 2270	FCM 3030	FCM 3046	FCM 4646
FCM High performance double glazing (RRP) \$	286	330	373	673	361	460	509

Custom-made flashings are not provided with FCM Skylight – VELUX can assist with technical advice and drawings.

Prices include flashing for single skylight (excludes FCM) into tile or metal roof. Contact VELUX Customer Services for details and prices of combi flashings for coupled skylights.
 Price list effective April 2010. All prices are supply only and include GST. Prices subject to change without notice. All prices quoted are Recommended Retail Prices (RRP) only.

Delivery time (in working days)*	NSW 1-2	VIC 1-2	SA 3	ACT 1-2	QLD 2-5	NT 3-7	TAS 3-5	WA 1-2†
----------------------------------	---------	---------	------	---------	---------	--------	---------	---------

*Metropolitan areas only. Subject to order being processed before 12 EST noon. †Subject to availability at Perth warehouse.

VELUX SKYLIGHTS & ROOF WINDOWS SIZE AVAILABILITY (mm's)

700	VS VSE FS (101) C01			VS VSE FS (601) S01
780	C02			
980	VS VSE FS GGL GHL (104) C04	VS VSE FS GGL GHL (304) M04		
1180		VS VSE FS GHL (306) M06	VS VSE FS (606) S06	
1400	VS VSE FS (108) C08	VS VSE FS GGL GHL (308) M08		
	◀ 550 ▶	◀ 780 ▶	◀ 1140 ▶	

Old codes shown in (brackets).

VELUX FLAT ROOF SKYLIGHTS SIZE AVAILABILITY (mm's)

665	FCM 2222			
870		FCM 3030		
970	FCM 2234			
1275	FCM 2246	FCM 3046	FCM 4646	
1885	FCM 2270			
	◀ 665 ▶	◀ 870 ▶	◀ 1275 ▶	▶

Bringing light to life™

VELUX Australia Pty Ltd
321-323 Princes Highway, PO Box 93, St Peters NSW 2044


Customer Services: Tel: 1300 859 856

Fax: (02) 9550 3289 E-mail: customer.service@VELUX.com.au

www.velux.com.au

VELUX®

SYDNEY HEAD OFFICE & SHOWROOM



OPENING TIMES:

Sydney Head Office: 8am-5pm (Mon-Fri)
Showroom: 8.30am-4.30pm (Mon-Fri)